

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
3 March 2005 (03.03.2005)

PCT

(10) International Publication Number
WO 2005/020514 A1

(51) International Patent Classification⁷: **H04L 12/28**

Carl [US/US]; 2360 Bridle Oak Drive, South Jordan, Utah 84095 (US). ARBUCKLE, Lynn, Howard [US/US]; 382 South 1000 East, Bountiful, Utah 84010 (US).

(21) International Application Number:
PCT/US2004/006357

(74) Agents: TRIPOLI, Joseph, S. et al.; 2 Independence Way, Suite 200, Princeton, NJ 08540 (US).

(22) International Filing Date: 2 March 2004 (02.03.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
60/495,656 15 August 2003 (15.08.2003) US

(71) Applicant (for all designated States except US): THOMSON LICENSING S.A. [FR/FR]; 46, Quai A. Le Gallo, F-92648 Boulogne (FR).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(72) Inventors; and

(75) Inventors/Applicants (for US only): CHRISTENSEN,

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),

[Continued on next page]

(54) Title: CHANGEABLE FUNCTIONALITY IN A BROADCAST ROUTER



(57) Abstract: There is provided a broadcast router that includes a plurality of input cards (410), a plurality of output cards (460), at least one programmable device (466), and a configuration control card (498). The plurality of input cards input data into the broadcast router. The plurality of output cards output the data from the broadcast router. The configuration control card stores configuration information for configuring the at least one programmable device to perform a first set of functions. The configuration control card is adapted for removal and replacement by at least one other configuration control card that stores other configuration information for configuring the at least one programmable device to perform a second set of functions having a difference from the first set of functions so as to change a functionality of the broadcast router.



Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

— *with international search report*